

TECHNICAL SHEET

FM11



FM Screw Compressors offer up to 46° ambient temperature. The generously sized ventilation system ensures optimum cooling, low outlet air temperatures best performance and reliability under harshest conditions. Optional 5 year extended warranty.

Main Features

- New advanced controller C-PRO 2.0
- Premium quality group air-ends
- Easy maintenance
- Compact design with footprint of 0.4 m2
- High efficient IE3 motors
- High capacities
- Pressures of 7, 8,10 and 13 bar

Part No.	CC1184133	CC1184154	CC1183627	CC1184155
Model/Modèle	FM11	FM11	FM11	FM11
Rec/Réservoir (l)	Floor	Floor	Floor	Floor
Drive/Régulation	Fixed	Fixed	Fixed	Fixed
Transmission/Accouplement	Belt	Belt	Belt	Belt
Dryer/Sécheur d'air	No	No	No	No
Power/Puissance (kW)	11	11	11	11
Power/Puissance (Hp / Ch)	15	15	15	15
Voltage/Tension (Volts)	400/50	400/50	400/50	400/50
FAD/Débit (m3/min)	1.59	1.58	1.39	1.09
FAD/Débit (Cfm)	56.15	55.80	49.09	38.49
Pressure/Pression maxi (Bar)	7	8	10	13
Pressure/Pression maxi (Psi)	102	116	145	188
Electronic Control/Contrôleur	C-Pro 2.0	C-Pro 2.0	C-Pro 2.0	C-Pro 2.0
Air Cooled/Refroidissement par air	Yes	Yes	Yes	Yes
After-Cooler/Radiateur	Yes	Yes	Yes	Yes
Noise level/Niveau sonore dB(A)	70	70	70	70
Port/Raccordement	3/4"	3/4"	3/4"	3/4"
Dimensions	667x630x1050	667x630x1050	667x630x1050	667x630x1050
Weight/Poids (kg)	219	219	219	219