

TECHNICAL SHEET

FM11RS

FM RS Variable Speed Drive Rotary Screw Compressors offer up to 46° ambient temperature.

The generously sized ventilation system ensures optimum cooling, low outlet air temperatures best performance and reliability under harshest conditions.

Optional 5 year extended warranty.



Main Features

- New advanced controller C-PRO 2.0
- Standard sequence control up to 8 units including variable speed
- Premium quality group air-ends
- Easy maintenance
- Compact design with footprint of 0.4 m2
- High efficient IE3 motors
- High capacities

Part No.	CC1184160	CC1184161	CC1184162	CC1184163
Model/Modèle	FM11RS	FM11RS	FM11RS	FM11RS
Rec/Réservoir (l)	Floor	Floor	Floor	Floor
Drive/Régulation	Variable	Variable	Variable	Variable
Transmission/Accouplement	Belt	Belt	Belt	Belt
Dryer/Sécheur d'air	No	No	No	No
Power/Puissance (kW)	11	11	11	11
Power/Puissance (Hp / Ch)	15	15	15	15
Voltage/Tension (Volts)	400/50	400/50	400/50	400/50
FAD/Débit (m3/min)	1.59	1.56	1.39	1.09
FAD/Débit (Cfm)	56.15	55.09	49.09	38.49
Pressure/Pression maxi (Bar)	7	8	10	13
Pressure/Pression maxi (Psi)	102	116	145	188
Electronic Control/Contrôleur	C-Pro 2.0	C-Pro 2.0	C-Pro 2.0	C-Pro 2.0
Air Cooled/Refroidissement par air	Yes	Yes	Yes	Yes
After-Cooler/Radiateur	Yes	Yes	Yes	Yes
Noise level/Niveau sonore dB(A)	67	67	67	67
Port/Raccordement	3/4"	3/4"	3/4"	3/4"
Dimensions	667x630x1050	667x630x1050	667x630x1050	667x630x1050
Weight/Poids (kg)	234	234	234	234