

TECHNICAL SHEET

FM15RS



FM RS Variable Speed Drive Rotary Screw Compressors offer up to 46° ambient temperature.

The generously sized ventilation system ensures optimum cooling, low outlet air temperatures best performance and reliability under harshest conditions.

Optional 5 year extended warranty.

Main Features

- New advanced controller C-PRO 2.0
- Standard sequence control up to 8 units including variable speed
- Premium quality group air-ends
- Easy maintenance
- Compact design with footprint of 0.55 m2
- High efficient IE3 motors
- High capacities

Part No.	CC1184272	CC1184273	CC1184274	CC1184275
Model/Modèle	FM15RS	FM15RS	FM15RS	FM15RS
Rec/Réservoir (l)	Floor	Floor	Floor	Floor
Drive/Régulation	Variable	Variable	Variable	Variable
Transmission/Accouplement	Belt	Belt	Belt	Belt
Dryer/Sécheur d'air	No	No	No	No
Power/Puissance (kW)	15	15	15	15
Power/Puissance (Hp / Ch)	20	20	20	20
Voltage/Tension (Volts)	400/50	400/50	400/50	400/50
FAD/Débit (m3/min)	2.64	2.46	2.2	1.75
FAD/Débit (Cfm)	93.23	86.87	77.69	61.80
Pressure/Pression maxi (Bar)	7	8	10	13
Pressure/Pression maxi (Psi)	102	116	145	188
Electronic Control/Contrôleur	C-Pro 2.0	C-Pro 2.0	C-Pro 2.0	C-Pro 2.0
Air Cooled/Refroidissement par air	Yes	Yes	Yes	Yes
After-Cooler/Radiateur	Yes	Yes	Yes	Yes
Noise level/Niveau sonore dB(A)	73	73	73	73
Port/Raccordement	1"	1"	1"	1"
Dimensions	787x698x1202	787x698x1202	787x698x1202	787x698x1202
Weight/Poids (kg)	360	360	360	360