

TECHNICAL SHEET FM22/CT/500



FM Screw Compressors offer up to 46° ambient temperature. The generously sized ventilation system ensures optimum cooling, low outlet air temperatures best performance and reliability under harshest conditions. Receiver mounted with refrigerated dryer. Optional filter pack with by-pass and 5 year extended warranty

Main Features

- New advanced controller C-PRO 2.0
- Premium quality group air-ends
- Easy maintenance
- Compact design with footprint of 1.6 m2
- High efficient IE3 motors
- High capacities
- Pressures of 7, 8,10 and 13 bar

Part No.	RSCCP2217V4	RSCCP2218V4	RSCCP2219V4	RSCCP2220V4
Model/Modèle	FM22/CT/500	FM22/CT/500	FM22/CT/500	FM22/CT/500
Rec/Réservoir (l)	500	500	500	500
Drive/Régulation	Fixed	Fixed	Fixed	Fixed
Transmission/Accouplement	Belt	Belt	Belt	Belt
Dryer/Sécheur d'air	Yes	Yes	Yes	Yes
Power/Puissance (kW)	22	22	22	22
Power/Puissance (Hp / Ch)	30	30	30	30
Voltage/Tension (Volts)	400/50	400/50	400/50	400/50
FAD/Débit (m3/min)	3.5	3.23	3.06	2.59
FAD/Débit (Cfm)	123.60	114.07	108.06	91.47
Pressure/Pression maxi (Bar)	7	8	10	13
Pressure/Pression maxi (Psi)	102	116	145	188
Electronic Control/Contrôleur	C-Pro 2.0	C-Pro 2.0	C-Pro 2.0	C-Pro 2.0
Air Cooled/Refroidissement par air	Yes	Yes	Yes	Yes
After-Cooler/Radiateur	Yes	Yes	Yes	Yes
Noise level/Niveau sonore dB(A)	74	74	74	74
Port/Raccordement	1"	1"	1"	1"
Dimensions	2000x800x1850	2000x800x1850	2000x800x1850	2000x800x1850
Weight/Poids (kg)	577	577	577	577